

Super Hand Dry Cutter 8320 - BIG²

with Ø 320/84T HM saw blade:

- Ideal for cutting sandwich panels, trapezoidal sheet, trunking and cable ducting, steel pipes and nonferrous metals, composite materials etc., up to cutting depth of 120 mm on guide rail
- Dry cutting without lubricant, instead of a chainsaw
- Guard closed, prevents flying chips to the user
- Integrated chip collector, connector for optional extraction device
- LED overload indicator:
green: ok | orange: warning | red: over load
- **Lightweight magnesium: 8,4 kg**
- **Cutting guide 1.400 mm with quick fixation**
- Ideal for clean and straight cutting of sandwich panels
- Delivered with 2 C-clamps



Specifications

Power input	1.800 W
Voltage	230V/50HZ or 115V/60Hz
No load speed	1.700 rpm
Net weight	8,4 kg
Blade size	320 mm
Cable	5 m

Super Hand Dry Cutter	Ref.
Super Hand Dry Cutter 8320 delivered with Ø 320/84T Saw blade 230V/115V	608270 / 608270 U
Super Hand Dry Cutter 8320 incl. Ø 320/84T Saw blade and Guide-Rail	608270SET

Saw Blades	Ref.
Cutting guide rail 1.400 mm	608275D
CT Saw blade Ø 320 x 2,2 x 1,8 x 25,4 x 84T	608276
CT Saw blade Ø 320 x 2,2 x 1,8 x 25,4 x 72T	608278
CT Saw blade Ø 320 x 2,2 x 1,8 x 25,4 x 84T for stainless steel - food & construction	608276NSF

