

MAGPRO 35 Adjust 1s & 2s

Huge stroke 85 - 230 mm, allows also the use of longer drills up to Ø 13 mm
 (with optional chuck Ref.: 490152A)

- 1 or 2 speeds
- Quick release
- Core drilling
- Twist drilling
- 17.000 N magnetic adhesion
- Overload protection
- Integrated cooling system



With a huge stroke and 1 or 2 speeds

Specifications

Power input	1.100 W
Voltage	230V/50HZ
Speed MAGPRO 35 Adjust 1s	450 / 270 rpm (no load / full load)
Speed MAGPRO 35 Adjust 2s	730 / 440 rpm (no load / full load)
Shank	Weldon 19 mm
Max. Ø core drills x L	12 - 35 x 50 mm
Max. Ø twist drills x L	13 x 140 mm
Stroke	85 mm for normal core drills, up to 230 mm for twist drills (with adapter and chuck)
Magnetic adhesion	17.000 N
Magnetic surface	175 x 90 mm
Cooling system	integrated, automatic
Net weight	14 kg (MAGPRO 35/1s) 15 kg (MAGPRO 35/2s)

Description	Ref.
MAGPRO 35 Adjust 1s - delivery in suitcase with quick release, safety chain and tools	490150 1
MAGPRO 35 Adjust 2s - delivery in suitcase with quick release, safety chain and tools	490150 2
Core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
Drill chuck and adapter 13 mm	490152A
Adapter with Weldon 19 mm (3/4") for Fein core drills with Quick-in shank including 1 ejector pin	490154
High Performance Cutting Oil Spray for optimal cooling and higher cutting performance (400 ml)	490020