

## MAGPRO 35 Semi Automatic

### Core drilling with automatic feed

- Automatic drilling for core drills from Ø 14 to 30 mm
- Hand operation from Ø 12 to 35 mm
- Automatic feed activation with crank handle

### Optional:

- Quick release
- 13 mm chuck with adapter
- Magnetic chip collector



### Specifications

|                         |  |
|-------------------------|--|
| Power input             | 1.100 W                                |
| Voltage                 | 230V/50HZ                              |
| Speeds                  | 620 / 350 rpm<br>(no load / full load) |
| Shank                   | Weldon 19 mm                           |
| Max. Ø core drills x L  | 12 - 35 x 50 mm                        |
| Max. Ø twist drills x L | 13 x 110 mm                            |
| Max. depth x Ø          | 50 x 35 mm<br>(Hand feed)              |
|                         | 45 x 30 mm<br>(Auto feed)              |
| Stroke                  | 70 mm                                  |
| Magnetic adhesion       | 15.000 N                               |
| Magnetic surface        | 165 x 80 mm                            |
| Cooling system          | integrated,<br>automatic               |
| Net weight              | 17 kg                                  |

| Description   | Ref.    |
|---|---------|
| <b>MAGPRO 35</b> - 230 V delivery in suitcase with safety chain and maintenance tools                 | 490180  |
| <b>Core drill set 30 mm</b> Ø 12, 14, 16, 18, 20, 22 mm with pilot pin                                | 490145  |
| <b>Drill chuck and adapter 13 mm</b>  | 490152A |
| <b>Quick release for MAGPRO 35</b>  | 490151  |
| <b>Magnetic chip collector</b>  | 490153  |
| <b>High Performance Cutting Oil Spray</b> for optimal cooling and higher cutting performance (400 ml) | 490020  |