

Hand Dry Cutter 8230N - the mobile²

with Ø 230/48T CT saw blade:

- Ideal for cutting metal sheets, sandwich panels, trapezoidal sheets, steel pipes & profiles, nonferrous metals and composite materials, optional with impact resistant LBS-blade
- By default fitted with a Ø 230/48T resharpenable CT-saw blade for highest cutting lifes at a high cutting quality
- Strong and light construction: 7,1 kg
- Chip collector for clean work
- No need of lubrication
- Maximum cutting depth 82/56 mm bevel cut and thickness 10 mm



Specifications

Motor output	1.700 W
Voltage	230V/50HZ or 115V/60Hz
No load speed	2.600 tpm
Net weight	7,1 kg
Blade size	230 mm
Cable	5 m

Maximum cutting capacities in mm

	90° Cutting	45° Bevel cut
Cutting depth	82	56
Square	82 x 10	56 x 8
Rectangular	82 x 5	56 x 4
	Ø 82 x 5	Ø 56 x 4

Description

Description	Ref.
230/48T standard saw blade	608280
230/60T LBS-blade impact resistant	608280LBS
230/48T for inox	608280I

Accessoires

Accessoires	Ref.
Guide rail with integrated clamping system	608284

Saw Blades

Saw Blades	Ref.
230/48T standard for steel	72123048
230/48T for steel / inox	72123048Y
230/48T - for stainless steel food & construction	72123048NSF
230/60T for aluminum	72123060
230/68T for thin walled material	72123068
230/84T for thin sheet metal	72123084
230/60T LBS-blade shock resistant	72223060