

## MAGPRO 40 2S

Generous stroke of 165 mm with adapter  
(enables, among other things, the use of longer drills)

- 2 speeds
- Core drilling
- Twist drilling
- 17.000 N magnetic adhesion
- Overload protection
- Integrated cooling system



With long stroke and 2 speeds

### Specifications

Power input	1.100 W
Voltage	230V/50HZ
Speed (no load / full load)	650 / 465 rpm 1100 / 790 rpm
Shank	Weldon 19 mm
Max. Ø core drills x L	12 - 40 x 55 mm
Max. Ø twist drills x L	13 x 140 mm
Stroke	85 mm for normal core drills, up to 165 mm for twist drills (with adapter and chuck)
Magnetic adhesion	17.000 N
Magnetic surface	175 x 85 mm
Cooling system	integrated, automatic
Net weight	13 kg

Description	Ref.
<b>MAGPRO 40 2S</b> - delivery in suitcase with quick release, safety chain and tools	490142
<b>Core drill set 30 mm Ø</b> 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
<b>Drill chuck and adapter 13 mm</b>	490152A
<b>Adapter with Weldon 19 mm (3/4")</b> for Fein core drills with Quick-in shank including 1 ejector pin	490154
<b>High Performance Cutting Oil Spray</b> for optimal cooling and higher cutting performance (400 ml)	490020