

MAGPRO 50/2s Adjust

Core drilling up to Ø 50 mm with a huge stroke and 2 speeds

- Huge stroke 85 - 230 mm
- 2 speeds
- Quick release
- Core drilling
- Twist drilling
- 17.000 N magnetic adhesion
- Overload protection
- Integrated cooling system



Specifications

| | |
|-------------------------|--|
| Power input | 1.100 W |
| Voltage | 230V/50HZ |
| Core & Twist drilling | 300 / 180 rpm 450 / 170 rpm (no load / full load) |
| Shank | Weldon 19 mm |
| Max. Ø core drills x L | 12 - 50 x 50 mm |
| Max. Ø twist drills x L | 13 x 140 mm |
| Stroke | 85 mm for normal core drills, up to 230 mm for twist drills (with adapter and stroke) |
| Magnetic adhesion | 17.000 N |
| Magnetic surface | 175 x 90 mm |
| Cooling system | integrated, automatic |
| Net weight | 15 kg |

| Description | Ref. |
|--|----------|
| MAGPRO 50/2s Adjust - delivery in suitcase with quick release, safety chain and maintenance tools | 490170 2 |
| Adapter with Weldon shank 19 mm (3/4") for Fein core drills with Quick-in shank including 1 ejector pin | 490154 |
| Core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin | 490145 |
| Drill chuck and adapter 13 mm | 490152A |
| Magnetic chip collector | 490153 |
| High Performance Cutting Oil Spray for optimal cooling and higher cutting performance (400 ml) | 490020 |