

## MAGPRO 80 4S

With a large stroke and 4 speeds

- 4 speeds for core drilling
- Solid drilling up to 16 mm
- Generous stroke of 270 mm
- enables, among other things, the use of longer fine drills
- 17.000 N Magnetic adhesion
- Overload protection
- Integrated cooling system



### Specifications

Power input	1.600 W
Voltage	230V/50HZ
Speed	190 / 105 rpm
(no load / full load)	300 / 165 rpm
	420 / 230 rpm
	660 / 365 rpm
Shank	CM3 - Weldon 19 mm
Max. Ø core drills x L	12 - 80 x 55 mm
Max. Ø twist drills x L	16 x 140 mm
Stroke	85 mm for normal core drills, up to 270 mm for twist drills (with adapter and chuck)
Magnetic adhesion	17.000 N
Magnetic surface	220 x 110 mm
Cooling system	integrated, automatic
Net weight	24 kg

### Description

Description	Ref.
<b>MAGPRO 80 4S</b> - delivery in suitcase with quick release, safety chain and tools	490184
<b>Core drill set 30 mm Ø</b> 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
<b>drill chuck 16 mm + MK3 adapter</b>	490164
<b>Weldon 32 MK3 adapter for core drills from Ø 61 mm</b>	490163
<b>Adapter with Weldon 19 mm (3/4")</b> for Fein core drills with Quick-in shank including 1 ejector pin	490154
<b>High Performance Cutting Oil Spray</b> for optimal cooling and higher cutting performance (400 ml)	490020