

MAGPRO 120/4s

The biggest allrounder with 4 speeds

- Core drilling up to Ø 120 mm
- The step-less adjustable electronic speed control enables an optimal adjustment of rotation speed too



Specifications	
Power input	2.000 W
Voltage	230V/50Hz
Speed (no load / full load)	1: 120 / 35 rpm 2: 220 / 70 rpm 3: 250 / 80 rpm 4: 450 / 140 rpm
Shank	Weldon 19/32 mm, MT3
Max. Ø core drills x L	12 - 120 x 75 mm
Max. Ø twist drills x L	16 x 110 mm
Max. Ø twist drills x L MT3	32 x 150 mm
Max. depth x Ø	75 x 120 mm
Stroke	100 mm
Magnetic adhesion	32.000 N
Magnetic surface	200 x 100 mm
Cooling system	integrated, automatic
Net weight	30 kg

Description	Ref.
MAGPRO 75/4s Swivel Base - 230V in suitcase with safety chain, maintenance tools and MT3/19 mm adapter for core drills Ø 12 - 60 mm and MT3/32 mm adapter for core drills Ø 61 mm	490100
MT3 Quick change adapter for thread cutter shank M3-M14	490162
Quick change inserts M3-M14 (single)	490162 M3-14
MT3 Quick change adapter for thread cutter shank M5-M22	490165
Quick change inserts M5-M22 (single)	490162 M5-22
Core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
Drill chuck 16 mm and adapter	490164
High Performance Cutting Oil Spray (400 ml)	490020