

Hand Dry Cutter 8230N - the mobile

with Ø 230/48T CT saw blade:

- Ideal for cutting metal sheets, sandwich panels, trapezoidal sheets, steel pipes & profiles, nonferrous metals and composite materials
- Optional with impact resistant LBS-blade for metal grids & grates
- By default fitted with a Ø 230/48T resharpenable CT-saw blade for highest cutting lifes at a high cutting quality
- Strong and light construction: 7,1 kg
- Chip collector for clean work
- No need of lubrication
- Maximum cutting depth **82/56 mm** bevel cut
- Cutting up to a thickness of **10 mm** at 90°



Specifications

| | |
|---------------|---------------------------|
| Motor output | 1.700 W |
| Voltage | 230V/50HZ or 115V/60Hz |
| No load speed | 2.600 tpm |
| Net weight | 7,1 kg |
| Blade size | 230 mm |
| Cable | 5 m |

Maximum cutting capacities in mm

| | 90° Cutting | 45° Bevel cut |
|---------------|-------------|---------------|
| Cutting depth | 82 | 56 |
| Square | 82 x 10 | 56 x 8 |
| Rectangular | 82 x 5 | 56 x 4 |
| Round | Ø 82 x 5 | Ø 56 x 4 |



72223060



608284

Description

| Description | Ref. |
|---|-----------|
| 230/48T for inox | 608280I |
| 230/60T LBS-blade impact resistant | 608280LBS |
| 230/48T for inox + guide rail with integrated clamping system | 608280ICG |

Saw Blades

| Saw Blades | Ref. |
|---|-------------|
| 230/48T standard for steel | 72123048 |
| 230/48T for steel / inox | 72123048Y |
| 230/48T - for stainless steel food & construction | 72123048NSF |
| 230/60T for aluminum | 72123060 |
| 230/68T for thin walled material | 72123068 |
| 230/84T for thin sheet metal | 72123084 |
| 230/60T LBS-blade shock resistant | 72223060 |

Accessoires (optional)

| Accessoires (optional) | Ref. |
|--|--------|
| Guide rail with integrated clamping system | 608284 |