

Premium Super Dry Cutter 9435 - The Reference

- Cuts ferrous and non-ferrous metal tubes, pipes and profiles made of mild steel, **stainless steel**, aluminium, plastic and composite materials
- No need of lubricant and manual deburring
- **Exclusive blade stabilising system** reduces vibrations
- High torque motor for continuous operation
- Panted quick-release vice for bevel cuts
- Heavy duty angle cutting at 90-75-60-45°
- Fitted with a Ø 355/90T CT saw blade
- Optional stand for a complete and save work place
- CE approved operating system



Specifications

Power input	2.400 W
Voltage	230V/50Hz or 115V/50Hz
No load speed	1.400 rpm
Net weight	25 kg
Blade size	355 mm

Maximum cutting capacities in mm

	90° Cutting	45° Miter Cut
Round	Ø 140 / in Inox 125	Ø 102
Square	125 x 125	80 x 80
Rectangular	105 x 155 90 x 180	75 x 100



600526T3



600546



609910

Premium Super Dry Cutter 9435 Ref.

with 355/90T Saw blade 230V	600560T3
with 355/90T Saw blade 115V	608301T3

HM saw blades Ref.

355/90T for stainless steel- food & construction	600570NSF
14"/120T for very thin steel and stainless steel	600512
355/90T for thin steel and stainless steel	600570
355/72T for medium steel and stain- less steel	600580
355/60T for thick steel and stainless steel	600590
355/60T for cast iron	600591
355/66T for mild steel	600595
355/96T for aluminum	600594

Accessories (optional)

Stand for PSDC 9435	600526T3
Thinfix- clamp for open profiles	600546
Eccentric clamping system	609910