

MAGPRO 50/2s Adjust

Core drilling up to Ø 50 mm with a huge stroke and 2 speeds

- Huge stroke 85 - 230 mm
- 2 speeds
- Quick release
- Core drilling
- Twist drilling
- 17.000 N magnetic adhesion
- Overload protection
- Integrated cooling system



Specifications

Power input	1.100 W
Voltage	230V/50HZ
Core & Twist drilling	300 / 180 rpm
	450 / 270 rpm (no load / full load)
Shank	Weldon 19 mm
Max. Ø core drills x L	12 - 50 x 50 mm
Max. Ø twist drills x L	13 x 140 mm
Stroke	85 mm for normal core drills, up to 230 mm for twist drills (with adapter and stroke)
Magnetic adhesion	17.000 N
Magnetic surface	175 x 90 mm
Cooling system	integrated, automatic
Net weight	15 kg

Description

Description	Ref.
MAGPRO 50/2s Adjust - delivery in suitcase with quick release, safety chain and maintenance tools	490170 2

Accessories (optional)

Adapter with Weldon shank 19 mm (3/4") for Fein core drills with Quick-in shank including 1 ejector pin	490154
Core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
Drill chuck and adapter 13 mm	490152A
Magnetic chip collector	490153
High Performance Cutting Oil Spray for optimal cooling and higher cutting performance (400 ml)	490020