

Hand Dry Cutter 8230 Air - air operated

with Ø230/48T HM saw blade

MADE
IN
GERMANY



DRY-CUT TECHNOLOGY
Dry cutting without lubricant

- Ideal for cutting metal sheets, sandwich panels, trapezoidal sheet, steel pipes and profiles, nonferrous metals and composite materials, optional with impact resistant LBS-saw blade
- Chip collector for clean work
- No need of lubrication
- Strong and light construction: 8,3 kg (without blade)
- Maximum cutting depth 82 / 56 mm bevel cut and thickness 10 mm



Specifications

	Operating pressure (flow pressure)	6 bar
	Motor output	1.500 W
	No load speed	1.700 rpm
	Air consumption	ca 2 m³/min
	Air connection	R ½" Female (Standard)
	ID of hose	> Ø 13 mm
	Net weight	8,6 kg
	Blade size	230 mm
	Noise level (1 m distance)	103,3 dB(A)
	Vibration level no load speed	< 2,5 m/s²

Maximum cutting capacities [mm]	90° Cutting	45° Bevel cut
Cutting depth	82	56
Square	82 x 10	56 x 8
Rectangular	82 x 5	56 x 4
Round	Ø 82 x 5	Ø 56 x 4



72223060



608284



Description

Ref.

Hand Dry Cutter 8320 -Air - delivered with Ø 230/48T saw blade + case 608100

Hand Dry Cutter 8320 -Air - delivered with Ø 230/60T LBS-Saw blade + case 608100LBS



Saw Blades

Ref.

Ø 230/48T - standard for steel	72123048
Ø 230/48T - for stainless steel / steel	72123048I
Ø 230/48T - for inox - food & construction	72123048NSF
Ø 230/60T - for aluminum	72123060
Ø 230/68T - for thin walled material	72123068
Ø 230/84T - for thin sheet metal	72123084
Ø 230/60T LBS-saw blade	72223060



Accessories (optional)

Ref.

Guide rail with integrated clamping system 608284