

Premium Dry Cutter 9430 - The best seller

- Cuts ferrous and non-ferrous metal tubes, pipes and profiles made of mild steel, aluminium, plastic and composite materials
- No need of lubricant and manual deburring
- High torque motor for continuous operation
- Gear box for easy blade changes
- Panted quick-release vice for bevel cuts
- Heavy duty angle cutting at 90-75-60-45°
- Fitted with a Ø 305/90T TCT saw blade
- Optional stand for a complete and save work place
- CE approved operating system



Specifications

Power input	2.400 W
Voltage	230V/50Hz or 115V/60Hz
No load speed	1.400 rpm
Nettogewicht	23 kg
Sägeblattgröße	305 mm

Maximal cutting capacities in mm

	90° Cutting	45° Miter cut
Round	Ø 115	Ø 85
Square	100 x 100	85 x 85
Rectangular	85 x 160	85 x 85

Premium Dry Cutter 9430

Ref.

with 305/60T saw blade 230V	600520T3
with 305/60T saw blade 115V	608800T3

TCT saw blades

Ref.

305/60T for steel, non-ferrous metal and composites	600530
305/60T for steel & inox	605530 40
305/60T for cast iron	600535
305/80T for thin pipes and profiles	600540

Accessories (optional)

Ref.

Stand for PDC 9430	600526T3
Thinfix- clamp for open profiles	600546
Eccentric clamping system	609910



600526T3



600546



609910