

MAGPRO 80 4S

With a large stroke and 4 speeds

- 4 speeds for core drilling
- Solid drilling up to 16 mm
- Generous stroke of 270 mm
- enables, among other things, the use of longer fine drills
- 17.000 N Magnetic adhesion
- Overload protection
- Integrated cooling system

Specifications

Power input	1.600 W
Voltage	230V/50HZ
Speed	190 / 105 rpm
(no load / full load)	300 / 165 rpm
	420 / 230 rpm
	660 / 365 rpm
Shank	MK3 - Weldon 19 mm
Max. Ø core drills x L	12 - 80 x 55 mm
Max. Ø twist drills x L	16 x 140 mm / 32 mm MK3
Stroke	85 mm for normal core drills, up to 270 mm for twist drills (with adapter and chuck)
Magnetic adhesion	17.000 N
Magnetic surface	220 x 110 mm
Cooling system	integrated, automatic
Net weight	24 kg



490145TiN



490153



490020



Description

Description	Ref.
MAGPRO 80 4S - delivery in suitcase with quick release, safety chain and tools	490184

Accessories (optional)

Accessories (optional)	Ref.
„GOLDFINGER“ TiN core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145TiN
HSS core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
Carbide core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490148
Drill chuck 16 mm + MK3 adapter	490164
Weldon 32 MK3 adapter for core drills from Ø 61 mm	490163
Adapter with Weldon 19 mm (3/4") for Fein core drills with Quick-in shank including 1 ejector pin	490154
Magnetic chip collector	490153
High Performance Cutting Oil Spray for optimal cooling and higher cutting performance (400 ml)	490020