

## Super Hand Dry Cutter 8320 with Ø 320/84T HM saw blade:



### DRY-CUT TECHNOLOGY

Dry cutting without lubricant

- Ideal for cutting **sandwich panels**, trapezoidal sheet, trunking and cable ducting, steel pipes and nonferrous metals, composite materials etc., up to **cutting depth of 120 mm on guide rail**
- Guard closed, prevents flying chips to the user
- Integrated chip collector, connector for optional extraction device
- LED overload indicator:  
**green: ok** | **orange: warning** | **red: over load**
- **Lightweight magnesium: 8,4 kg**  
**Cutting guide 1.400 mm with quick fixation**
- Ideal for clean and straight cutting of sandwich panels
- Delivered with 2 C-clamps



### Specifications

Power input	1.800 W
Voltage	230V/50HZ or 115V/60Hz
No load speed	1.700 rpm
Net weight	8,4 kg
Blade size	320 mm
Cable	5 m

### Super Hand Dry Cutter Ref.

Super Hand Dry Cutter 8320 delivered with Ø 320/84T Saw blade 230V/115V 608270 / 608270 U

Super Hand Dry Cutter 8320 incl. Ø 320/84T Saw blade and Guide-Rail set 608270SET

### HM saw blades

Ref.

CT Saw blade Ø 320 x 2,2 x 1,8 x 25,4 x 84T	608276
CT Saw blade Ø 320 x 2,2 x 1,8 x 25,4 x 72T	608278
CT Saw blade Ø 320 x 2,2 x 1,8 x 25,4 x 84T for stainless steel - food & construction	608276NSF

### Accessories (optional)

Cutting guide rail 1.400 mm	608275D
Cutting guide rail 1.400 mm + 2 C-clamps	608275SET
Heavy Duty Professional Blow Case	60827BOX



608270SET



60827BOX