

Hand Dry Cutter 8200 - The mobile

with Ø 203/42T CT saw blade:



DRY-CUT TECHNOLOGY

Dry cutting without lubricant

- Ideal for cutting steel, metal sheets, sandwich panels, steel pipes & profiles, nonferrous metals and composite materials
- (optional with shock resistant LBS-blade)
- By default fitted with a Ø 203/42T resharpenable CT-saw blade for cutting steel and inox
- Chip collector for clean work
- No need of lubrication
- Maximum cutting depth 67/42 mm bevel cut and thickness 10 mm



Specifications

Power input	1.700 W
Voltage	230V/50HZ
No load speed	3.700 tpm
Net weight	6,3 kg
Blade size	203 mm
Cable	5 m

Maximum cutting capacities in mm

	90° Cutting	45° Bevel cut
Cutting depth	67	42
Angle	67 x 10	42 x 8
Rectangular	67 x 5	42 x 4
Round	67 x 5	42 x 4
Plain	10	8

Hand Dry Cutter 8200 230 V with:	Ref.
203/42T for steel + inox	608295
203/48T LBS-blade shock resistant	608295LBS

HM Saw Blades	Ref.
203/42T for steel + inox	72120042I
200/48T for aluminium	72120048A
203/48T LBS-blade shock resistant	72220348
203/70T for thin walled material & corrugated metal sheets	72120070



72220348