

MAGPRO 40 2S

Generous stroke of 165 mm with adapter
(enables, among other things, the use of longer drills)

- 2 speeds
- Core drilling
- Twist drilling
- 17.000 N magnetic adhesion
- Overload protection
- Integrated cooling system



With long stroke and 2 speeds

Specifications

Power input	1.100 W
Voltage	230V/50HZ
Speed	650 / 465 rpm (no load / full load)
Shank	Weldon 19 mm
Max. Ø core drills x L	12 - 40 x 55 mm
Max. Ø twist drills x L	13 x 140 mm
Stroke	85 mm for normal core drills, up to 165 mm for twist drills (with adapter and chuck)
Magnetic adhesion	17.000 N
Magnetic surface	175 x 85 mm
Cooling system	integrated, automatic
Net weight	13 kg

Description	Ref.
MAGPRO 40 2S - delivery in suitcase with quick release, safety chain and tools	490142

Accessories (optional)	Ref.
HSS cobalt core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
Carbide tipped core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490148
Chuck 13 mm - Weldon 19 mm	490152A
Adapter with Weldon 19 mm (3/4") for Fein core drills with Quick-in shank including 1 ejector pin	490154
Magnetic chip collector	490153
High Performance Cutting Oil Spray for optimal cooling and higher cutting performance (400 ml)	490020

