

MAGPRO 120/4s

The biggest allrounder with 4 speeds

- Core drilling up to Ø 120 mm
- The step-less adjustable electronic speed control enables an optimal adjustment of rotation speed too

Description

Ref.

MAGPRO 75/4s Swivel Base - 230V in suitcase with safety chain, maintenance tools and MT3/19 mm adapter for core drills Ø 12 - 60 mm and MT3/32 mm adapter for core drills Ø 61mm

Specifications

Power input 2.000 W

Voltage 230V/50Hz

Speed (no load / full load)

1:	120 / 35 rpm
2:	220 / 70 rpm
3:	250 / 80 rpm
4:	450 / 140 rpm

Shank Weldon 19/32 mm, MT3

Max. Ø core drills x L 12 - 120 x 75 mm

Max. Ø twist drills x L 16 x 110 mm

Max. Ø twist drills x L MT3 32 x 150 mm

Max. depth x Ø 75 x 120 mm

Stroke 100 mm

Magnetic adhesion 32.000 N

Magnetic surface 200 x 100 mm

Cooling system integrated, automatic

Net weight 30 kg



Accessories (optional)

Ref.

„GOLDFINGER“ TiN core drill set
30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin 490145TiN

HSS core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin 490145

Carbide core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin 490148

MT3 Quick change adapter for thread cutter shank M3-M14 490162

Quick change inserts M3-M14 (single) 490162 M3-14

MT3 Quick change adapter for thread cutter shank M5-M22 490165

Quick change inserts M5-M22 (single) 490165 M5-22

Drill chuck 16 mm and adapter 490164

Magnetic chip collector 490153

High Performance Cutting Oil Spray for optimal cooling and higher cutting performance (400 ml) 490020



490145TiN



490153



490020