

## MAGPRO 52 Air

Air-operated magnetic drill with a huge stroke

- Air-operated magnetic drill for work in hazardous and wet environments
- ATEX/ CEN approved, no electric!
- Core drilling up to Ø 52 mm
- Twist drilling up to Ø 13 mm
- Huge stroke up to 260 mm
- Magnetic adhesion: 8.000 N
- Integrated cooling system

### Specifications

Operating pressure	6 bar
Motor output	1.000 W
Speeds	400/ 200 rpm (no load/full load)
Air consumption	1,8 m <sup>3</sup> / min
Air connection	R 3/8" Female
Shank	Weldon 19 mm
Max. Ø core drills	52 mm
Max. Ø twist drills	13 mm
Stroke	260 mm
Magnetic adhesion	8.000 N
Magnetic surface	216 x 86 mm
Cooling system	automatic, external
Net weight	21,5 kg



### Description

Description	Ref.
MAGPRO 52 Air - Delivery in suitcase with safety chain, maintenance tools and pressurized lubrication system	490000

### Accessories (optional)

Accessories (optional)	Ref.
„GOLDFINGER“ TiN core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145TiN
HSS core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
Carbide core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490148
Drill chuck and adapter 13 mm	490152A
Magnetic chip collector	490153
High Performance Cutting Oil Spray for optimal cooling and higher cutting performance (400 ml)	490020



490145TiN



490153



490020