

Premium Dry Cutter 9430 - The best seller

with Ø 305/60T HM saw blade:



DRY-CUT TECHNOLOGY

Dry cutting without lubricant

- Cuts ferrous and non-ferrous metal tubes, pipes and profiles made of mild steel, aluminium, plastic and composite materials
- No need of lubricant and manual deburring
- High torque motor for continuous operation
- Gear box for easy blade changes
- Painted quick-release vice for bevel cuts
- Heavy duty angle cutting at 90-75-60-45°
- Optional stand for a complete and save work place
- CE approved operating system



Specifications

Power input	2.400 W
Voltage	230V/50Hz
No load speed	1.400 rpm
Nettogewicht	23 kg
Sägeblattgröße	305 mm

Maximal cutting capacities in mm

	90° Cutting	45° Miter cut
Round	Ø 115	Ø 85
Square	100 x 100	85 x 85
Rectangular	85 x 160	85 x 85

Premium Dry Cutter 9430

Ref.

with 305/60T saw blade 230V

600520T3

TCT saw blades

Ref.

305/60T for steel, non-ferrous metal and composites

600530

305/60T for steel & inox

605530 40

305/60T for cast iron

600535

305/80T for thin pipes and profiles

600540

Accessories (optional)

Ref.

Stand for PDC 9430

600526T3

Thinfix- clamp for open profiles

600546

Eccentric clamping system

609910



600526T3



600546



609910