

## **SUPER HAND DRY CUTTER 8320** THE BIGGEST





## Metal cutting circular saw by Jepson Power for fast and low-burr sawing of sandwich panels and trapezoidal sheets without cooling

- Ideal for cutting sandwich panels, trapezoidal sheet, trunking and cable ducting, steel pipes and nonferrous metals, composite materials etc., up to a cutting depth of 120 mm on guide rail
- Dry cutting without lubricant
- Closed construction of the blade guard prevents flying chips to the user
- Integrated chip collector, connector for optional extraction device
- LED overload indicator: green: ok. flashing red: warning | red: over load
- Lightweight magnesium: 8,4 kg (without saw blade)
- Ideal for clean and straight cutting of sandwich panels
- Optional: Guide rail 1.400 mm delivered with 2 C-clamps
- incl. Ø 320 mm / 84T carbide tipped saw blade



Optional:

Ref. 60827Box



Examples of cuts Transport case with wheels



Quick fixation



Depth adjustment with scaling



Connector for connecting 2 guide rails Ref. 608275B

Power input	Voltage	No load speed	Net weight	Blade size	Bore	Cable length
1.800 W	230V/50Hz or 115V/60HZ	1.700 min <sup>-1</sup>	8,4 kg	Ø 320 mm	Ø 25,4	5 m
Super Hand Dry Cutter 8320			Reference	Accessories		Reference
with Ø 320/84T saw blade 230V			608270	Guide rail 1.400 mm	608275D	
with Ø 320/84T saw blade 115V			608270 U	Guide rail set 1.400 mm		608275SET
with Ø 320/84T saw blade 230V + with guide rail 1.400 mm incl. 2 quick release clamps			608270SET	incl. 2 quick release clamp Heavy duty professional b	60827Box	
Saw blades			Reference	Connector for guide rail		608275B
320/84T for sandwich panels and steel			608276	Quick release clamp for gu	608275S	
320/72T for thick walled material			608278	Man and in a second it is a		
Ø 320/84T steel and stainless steel - coated food and construction			608276NSF	Max. cutting capacities		90°
				Round		120 x 6 mm

Square

Rectangular



120 x 120 x 6 mm 120 x 120 x 6 mm