



MAGPRO 120/4S

The biggest allrounder with 4 speeds

- Core drilling up to Ø 120 mm
- The stepless adjustable electronic speed control also enables an optimal adjustment of rotation speed

Scope of delivery:

Lashing strap, coolant container, tools, chip protection, ejector wedge, carry case, Weldon 19, CM3, Weldon 32



Transport case with wheels



Optional: CM3 Quick change adapter for thread cutter shank M5-M22 Ref. 490165



Core drilling



Thread cutting



Twist drilling with CM3-adapter

Technical specifications	
Power input	2000 W
Voltage	230 V / 50 Hz
No load / full load speeds	1: 120 / 35 min ⁻¹ 2: 220 / 70 min ⁻¹ 3: 250 / 80 min ⁻¹ 4: 450 / 140 min ⁻¹
Shank	19/32 mm Weldon, MT3
Max. Ø core drills x L	12 - 120 x 75 mm
Max. Ø twist drills x L	16 x 110 mm
Max. Ø twist drills x L MT3	32 x 150 mm
Max. Ø countersinks	63 mm
Max. drilling depth x Ø	75 x 120 mm
Tapping	M4-M22
Stroke	100 mm
Magnetic adhesion	32.000 N
Magnetic surface	200 x 100 mm
Cooling system	integrated, automatic
Net weight	30 kg

Description	Reference
Delivery in a carry case with safety chain, maintenance tools and CM3/19 mm adapter for core drills Ø 12 - 60 mm and CM3/32 mm adapter for core drills Ø 61mm	490100
Accessories (optional)	
HSS-co core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm + pilot pin	490145
Carbide core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm + pilot pin	490148
„Goldfinger“ TiN core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm + pilot pin	490145TiN
MT3 Quick change adapter for thread cutter shank M4-M14	490162
Quick change inserts M3-M14 (single)	490162 M3-14
MT3 Quick change adapter for thread cutter shank M5-M22	490165
Quick change inserts M5-M22 (single)	490165 M5-22
Drill chuck 16 mm and adapter	490164
Magnetic chip collector	490153
High performance cutting oil spray for optimal cooling and higher cutting performance (400 ml)	490020
HSS-countersinks with Weldon 19 shank on page 61	