

MAGPRO 60 M20

PRIME
LINE



Core drilling up to Ø 60 mm
Twist drilling up to Ø 23 mm
Thread cutting up to M20

- 6-speed motor
- Improved magnetic adhesion
- Quick and easy conversion to twist drilling thanks to the MT2 arbor

Scope of delivery:

Steel case, arbor for core drills, safety chain, carabina, hexagon key, pilot pins short/long



SPRING 2024



Thread cutting, twist- & core drilling
(accessories might be necessary)



Delivery in a carry case



MT2 arbor for quick and easy
conversion to twist drilling



Optional: drill chuck 16 mm
and adapter Art. 490164MK2

Technical specifications	
Power input	1.550 W
Voltage	230 V / 50 Hz
No load speeds	140 / 190 / 240 / 330 / 445 / 565 min ⁻¹
Shank	MT2
Core drill max. Ø x L	60 mm
Max. Ø twist drills x L	16 x 110 mm
Max. Ø twist drills x L MT2	23 x 150 mm
Max. thread cutting	M5 - M20
Stroke	190 mm
Magnet on 1" plate (dead lift)	15.300N
Net weight	17 kg
Height	430 (620) mm
Width	200 mm
Length	260 mm

Description	Reference
Magpro 60M20 - delivery in steel case, arbor for core drills, safety chain, carabina, hexagon key, pilot pins short/long	491170M20
Accessories (optional)	
HSS-Co core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145
Carbide tipped core drill set 30 mm Ø 1x12, 1x14, 1x16, 1x18, 1x20, 1x22 mm + pilot pin	490148
Gold finger core drill set TiN-coated 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145TiN
HSS-Co core drill set Ø 9/16", 5/8", 11/16", 3/4", 13/16", 15/16" x 1 + pilot pin	490145IN
Drill chuck and adapter 16 mm for MT2 arbor	490164MK2
Magnetic chip collector	490153
High-performance drilling and cutting oil spray for optimal cooling and higher cutting performance (Content: 400 ml)	490020
HSS-countersinks with Weldon 19 shank on page 69	