



# MAGPRO 60/2S



**Core drilling up to Ø 60 mm**  
**Twist drilling up to Ø 23 mm**

- 2-speed motor
- Improved magnetic adhesion
- Quick and easy conversion to twist drilling thanks to the MT2 arbor

**Scope of delivery:**

Steel case, arbor for core drills, safety chain, carabina, hexagon key, pilot pins short/long



Delivery in a carry case



MT2 arbor for quick and easy conversion to twist drilling



Optional: magnetic chip collector - Ref. 490153



Optional: drill chuck 16 mm and adapter Art. 490164MK2

Technical specifications	
Power input	1.550 W
Voltage	230 V / 50 Hz
No load speed	1: 250 / 135 min <sup>-1</sup> 2: 605 / 330 min <sup>-1</sup>
Shank	MT2
Core drill max. Ø x L	60 mm
Max. Ø twist drills x L	16 x 110 mm
Max. Ø twist drills x L MT2	23 x 150 mm
Stroke	190 mm
Magnet on 1" plate (dead lift)	15.300N
Net weight	17 kg
Dimensions [mm]	430 (620) x 200 x 260

Description	Reference
Magpro 60/2S - delivery in steel case, arbor for core drills, safety chain, carabina, hexagon key, pilot pins short/long	491170N
Accessories (optional)	
HSS-Co core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145
Carbide tipped core drill set 30 mm Ø 1x12, 1x14, 1x16, 1x18, 1x20, 1x22 mm + pilot pin	490148
Gold finger core drill set TiN-coated 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145TiN
HSS-Co core drill set Ø 9/16", 5/8", 11/16", 3/4", 13/16", 15/16" x 1 + pilot pin	490145IN
Drill chuck 13 mm and adapter for Weldon 19 arbor	490152A
Drill chuck 13 mm and adapter for MT2 arbor	490164MK2
Magnetic chip collector	490153
High-performance drilling and cutting oil spray for optimal cooling and higher cutting performance (Content: 400 ml)	490020

HSS-countersinks with Weldon 19 shank on **page 69**